

PRODUCT SPECIFICATION

Description

048 BUFFING is used in the construction of the cushion layer in unitary safety surfacing systems as well as the bottom layer in factory molded rubber safety tiles.

048 BUFFING is produced through a state of the art recycling process that removes contaminants and produces a mixture of controlled sizes that are ideal for field manufactured poured in place rubber surfacing as well as compression molded rubber tiles produced in a factory environment.

Benefits

- ✓ **Non Toxic:** Certified Safe by UC Berkeley and The Corporation for Manufacturing Excellence
- ✓ **Environmentally Friendly:** reduces the number of waste tires disposed in land fills
- ✓ **Locally Produced:** Reduces green house gas emissions through reduced transportation and reduces freight costs.
- ✓ **Quality:** Consistent quality delivered through state of art recycling process backed by an industry leader with more than 20 years experience.

Packaging

50LB Bags or 2,000LB Sacks

Physical Characteristics

CHEMICAL PROPERTIES	MIN	MAX
Acetone Extract	12	22
Ash	0	8
Carbon Black	26	35
Rubber Hydrocarbon	45	60

SIEVE SIZE	% RETAINED	
1/4"	0%	- 2%
8 Mesh	30%	- 60%
16 Mesh	60%	- 95%
20 Mesh	75%	- 100%
30 Mesh	98%	- 100%

- Test Method 100 grams, 10 minutes, Rotap Shaker

- Values "typical", custom blends available to meet any specification requirement.

WWW.BASRECYCLING.COM

BAS RECYCLING INC
14050 Day Street
Moreno Valley, CA 92553



1 (951) 214-6590